



Computer Engineering Department

Reinforcement Learning: Advanced Policy Gradients


Mohammad Hossein Rohban, Ph.D.

Spring 2025


Courtesy: Most of slides are adopted from CS 285 Berkeley.

Model-Free RL

- Value-based methods
 - Learnt value function
 - Implicit policy
- Policy-based methods
 - No value function
 - Learnt policy
- Actor-critic methods
 - Learnt value function
 - Learnt policy



Overview of Modern RL Methods




Policy Gradient Intuition

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \left(\sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \right) \left(\sum_{t=1}^T r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) \right)$$

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \underbrace{\nabla_{\theta} \log \pi_{\theta}(\tau_i)}_T r(\tau_i) \sum_{t=1}^T \nabla_{\theta} \log_{\theta} \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t})$$

maximum likelihood: $\nabla_{\theta} J_{\text{ML}}(\theta) \approx \frac{1}{N} \sum_{i=1}^N \nabla_{\theta} \log \pi_{\theta}(\tau_i)$

- Good stuff is made more likely
- Bad stuff is made less likely
- Simply formalizes the notion of “trial and error”!



Bias and Variance of Policy Gradient

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \nabla_{\theta} \log \pi_{\theta}(\tau_i) \boxed{r(\tau_i)}$$

The main source
of high variance



- Unbiased estimation:

$$E \left[\frac{1}{N} \sum_{i=1}^N \nabla_{\theta} \log \pi_{\theta}(\tau_i) r(\tau_i) \right] = \nabla_{\theta} J(\theta)$$

- But suffers from **high variance**!

Reducing Variance

- Everything in the gradient whose **expected is zero** could be removed, without affecting the optimization, but could lead to **lower gradient variance!**
- Causality trick
- Discount factor
- Baseline
- Actor-critic
- Optimization techniques:
 - Natural gradient
 - Trust region

Reducing Variance: Causality


$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \left(\sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \right) \left(\sum_{t=1}^T r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) \right)$$

Causality: policy at time t' cannot affect reward at time t when $t < t'$

$$\frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \left(\sum_{\substack{t'=1 \\ \text{red circle}}}^T r(\mathbf{a}_{i,t'}, \mathbf{s}_{i,t'}) \right)$$

$$\frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \left(\sum_{\substack{t'=t \\ \text{red circle}}}^T r(\mathbf{a}_{i,t'}, \mathbf{s}_{i,t'}) \right)$$


“reward to go” $\hat{Q}_{i,t}$



Reducing Variance: Discount Factor

option 1:
$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \left(\sum_{t'=t}^T \gamma^{t'-t} r(\mathbf{s}_{i,t'}, \mathbf{a}_{i,t'}) \right)$$

option 2:
$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \left(\sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \right) \left(\sum_{t=1}^T \gamma^{t-1} r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) \right)$$



Not the same

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \left(\sum_{t'=t}^T \gamma^{t'-t} r(\mathbf{s}_{i,t'}, \mathbf{a}_{i,t'}) \right)$$

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \boxed{\gamma^{t-1}} \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \left(\sum_{t'=t}^T \gamma^{t'-t} r(\mathbf{s}_{i,t'}, \mathbf{a}_{i,t'}) \right)$$


Reducing Variance: Baselines

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \nabla_{\theta} \log p_{\theta}(\tau) [r(\tau) - b]$$

$$b = \frac{1}{N} \sum_{i=1}^N r(\tau)$$

a convenient identity

$$p_{\theta}(\tau) \nabla_{\theta} \log p_{\theta}(\tau) = \nabla_{\theta} p_{\theta}(\tau)$$




$$E[\nabla_{\theta} \log p_{\theta}(\tau) b] = \int p_{\theta}(\tau) \nabla_{\theta} \log p_{\theta}(\tau) b d\tau = \int \nabla_{\theta} p_{\theta}(\tau) b d\tau = b \nabla_{\theta} \int p_{\theta}(\tau) d\tau = b \nabla_{\theta} 1 = 0$$

subtracting a baseline is *unbiased* in expectation!

average reward is *not* the best baseline, but it's pretty good!

Reducing Variance: Baselines

Faster convergence:




Reducing Variance: Review

- Exploiting causality
 - Future doesn't affect the past
- Discount factor
 - Two different version
- Baselines
 - Analyzing variance for deriving optimal baselines
- Now: Introducing actor-critic methods!


Policy Gradients so Far

REINFORCE algorithm:

- 
1. sample $\{\tau^i\}$ from $\pi_\theta(\mathbf{a}_t|\mathbf{s}_t)$ (run the policy)
 2. $\nabla_\theta J(\theta) \approx \sum_i \left(\sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_t^i|\mathbf{s}_t^i) \left(\sum_{t'=t}^T r(\mathbf{s}_{t'}^i, \mathbf{a}_{t'}^i) \right) \right)$
 3. $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t}|\mathbf{s}_{i,t}) \underbrace{\hat{Q}_{i,t}^\pi}_{\text{"reward to go"}}$$

“reward to go”



Improving Estimation of Reward to Go

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \underbrace{\left(\sum_{t'=1}^T r(\mathbf{s}_{i,t'}, \mathbf{a}_{i,t'}) \right)}$$


$\hat{Q}_{i,t}$: estimate of expected reward if we take action $\mathbf{a}_{i,t}$ in state $\mathbf{s}_{i,t}$

How to make a better estimate?

$Q(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_{\theta}} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$: true *expected* reward-to-go

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \underline{Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})}$$

much lower variance!




Improving Estimation of Reward to Go

Further improvement: Adding a baseline!

$Q(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$: true *expected* reward-to-go

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) (Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) - b_t)$$

$$b_t = \frac{1}{N} \sum_i Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$



Improving Estimation of Reward to Go


Further improvement: Adding a baseline!

$Q(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$: true *expected* reward-to-go

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) (Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) - V(\mathbf{s}_{i,t}))$$

$$b_t = \frac{1}{N} \sum_i Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$

$$\downarrow$$
$$V(\mathbf{s}_t) = E_{\mathbf{a}_t \sim \pi_\theta(\mathbf{a}_t | \mathbf{s}_t)} [Q(\mathbf{s}_t, \mathbf{a}_t)]$$



Advantage Value

$Q^\pi(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$: total reward from taking \mathbf{a}_t in \mathbf{s}_t

$V^\pi(\mathbf{s}_t) = E_{\mathbf{a}_t \sim \pi_\theta(\mathbf{a}_t | \mathbf{s}_t)} [Q^\pi(\mathbf{s}_t, \mathbf{a}_t)]$: total reward from \mathbf{s}_t

$A^\pi(\mathbf{s}_t, \mathbf{a}_t) = Q^\pi(\mathbf{s}_t, \mathbf{a}_t) - V^\pi(\mathbf{s}_t)$: how much better \mathbf{a}_t is

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) A^\pi(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$



the better this estimate, the lower the variance

Advantage Value Approximation

$$Q^\pi(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$$

$$V^\pi(\mathbf{s}_t) = E_{\mathbf{a}_t \sim \pi_\theta(\mathbf{a}_t | \mathbf{s}_t)} [Q^\pi(\mathbf{s}_t, \mathbf{a}_t)]$$


$$A^\pi(\mathbf{s}_t, \mathbf{a}_t) = Q^\pi(\mathbf{s}_t, \mathbf{a}_t) - V^\pi(\mathbf{s}_t)$$

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) A^\pi(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$

$$Q^\pi(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$$

$$= r(\mathbf{s}_t, \mathbf{a}_t) + \underbrace{\sum_{t'=t+1}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]}$$

$$\approx V^\pi(\mathbf{s}_{t+1})$$




Advantage Value Approximation

$$Q^\pi(\mathbf{s}_t, \mathbf{a}_t) \approx r(\mathbf{s}_t, \mathbf{a}_t) + V^\pi(\mathbf{s}_{t+1})$$

$$A^\pi(\mathbf{s}_t, \mathbf{a}_t) \approx r(\mathbf{s}_t, \mathbf{a}_t) + V^\pi(\mathbf{s}_{t+1}) - V^\pi(\mathbf{s}_t)$$

let's just fit $V^\pi(\mathbf{s})$!



Policy Evaluation

$$V^\pi(\mathbf{s}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t]$$

$$J(\theta) = E_{\mathbf{s}_1 \sim p(\mathbf{s}_1)} [V^\pi(\mathbf{s}_1)]$$


how can we perform policy evaluation?

Monte Carlo policy evaluation (this is what policy gradient does)

$$V^\pi(\mathbf{s}_t) \approx \sum_{t'=t}^T r(\mathbf{s}_{t'}, \mathbf{a}_{t'})$$

$$V^\pi(\mathbf{s}_t) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t'=t}^T r(\mathbf{s}_{t'}, \mathbf{a}_{t'})$$

(requires us to reset the simulator)



Policy Evaluation

Monte Carlo estimation with function approximator:



$$V^\pi(\mathbf{s}_t) \approx \sum_{t'=t}^T r(\mathbf{s}_{t'}, \mathbf{a}_{t'})$$

not as good as this: $V^\pi(\mathbf{s}_t) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t'=t}^T r(\mathbf{s}_{t'}, \mathbf{a}_{t'})$

but still pretty good!

training data: $\left\{ \left(\mathbf{s}_{i,t}, \underbrace{\sum_{t'=t}^T r(\mathbf{s}_{i,t'}, \mathbf{a}_{i,t'})}_{y_{i,t}} \right) \right\}$

supervised regression: $\mathcal{L}(\phi) = \frac{1}{2} \sum_i \left\| \hat{V}_\phi^\pi(\mathbf{s}_i) - y_i \right\|^2$



Policy Evaluation

How to make a better estimate?

$$\text{ideal target: } y_{i,t} = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_{i,t}] \approx r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) + V^\pi(\mathbf{s}_{i,t+1}) \approx r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) + \underbrace{\hat{V}_\phi^\pi(\mathbf{s}_{i,t+1})}$$

$$\text{Monte Carlo target: } y_{i,t} = \sum_{t'=t}^T r(\mathbf{s}_{i,t'}, \mathbf{a}_{i,t'})$$

directly use previous fitted value function!

Policy Evaluation

Bootstrap Estimation with Function Approximator

ideal target: $y_{i,t} = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_{i,t}] \approx r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) + \hat{V}_\phi^\pi(\mathbf{s}_{i,t+1})$


training data: $\left\{ \left(\mathbf{s}_{i,t}, \underbrace{r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) + \hat{V}_\phi^\pi(\mathbf{s}_{i,t+1})}_{y_{i,t}} \right) \right\}$

supervised regression: $\mathcal{L}(\phi) = \frac{1}{2} \sum_i \left\| \hat{V}_\phi^\pi(\mathbf{s}_i) - y_i \right\|^2$


Batch Actor-Critic Algorithm

batch actor-critic algorithm:

1. sample $\{\mathbf{s}_i, \mathbf{a}_i\}$ from $\pi_\theta(\mathbf{a}|\mathbf{s})$ (run it on the robot)
2. fit $\hat{V}_\phi^\pi(\mathbf{s})$ to sampled reward sums
3. evaluate $\hat{A}^\pi(\mathbf{s}_i, \mathbf{a}_i) = r(\mathbf{s}_i, \mathbf{a}_i) + \hat{V}_\phi^\pi(\mathbf{s}'_i) - \hat{V}_\phi^\pi(\mathbf{s}_i)$
4. $\nabla_\theta J(\theta) \approx \sum_i \nabla_\theta \log \pi_\theta(\mathbf{a}_i|\mathbf{s}_i) \hat{A}^\pi(\mathbf{s}_i, \mathbf{a}_i)$
5. $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$




$$V^\pi(\mathbf{s}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t]$$




Actor-Critic Algorithm: Architecture Design

batch actor-critic algorithm:

- 
1. sample $\{\mathbf{s}_i, \mathbf{a}_i\}$ from $\pi_\theta(\mathbf{a}|\mathbf{s})$ (run it on the robot)
 2. fit $\hat{V}_\phi^\pi(\mathbf{s})$ to sampled reward sums
 3. evaluate $\hat{A}^\pi(\mathbf{s}_i, \mathbf{a}_i) = r(\mathbf{s}_i, \mathbf{a}_i) + \hat{V}_\phi^\pi(\mathbf{s}'_i) - \hat{V}_\phi^\pi(\mathbf{s}_i)$
 4. $\nabla_\theta J(\theta) \approx \sum_i \nabla_\theta \log \pi_\theta(\mathbf{a}_i|\mathbf{s}_i) \hat{A}^\pi(\mathbf{s}_i, \mathbf{a}_i)$
 5. $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$


two network design



+ simple & stable


- no shared features between actor & critic

shared network design




Actor-Critic Algorithm: Batch vs. Online

batch actor-critic algorithm:

- 
1. sample $\{\mathbf{s}_i, \mathbf{a}_i\}$ from $\pi_\theta(\mathbf{a}|\mathbf{s})$ (run it on the robot)
 2. fit $\hat{V}_\phi^\pi(\mathbf{s})$ to sampled reward sums
 3. evaluate $\hat{A}^\pi(\mathbf{s}_i, \mathbf{a}_i) = r(\mathbf{s}_i, \mathbf{a}_i) + \gamma \hat{V}_\phi^\pi(\mathbf{s}'_i) - \hat{V}_\phi^\pi(\mathbf{s}_i)$
 4. $\nabla_\theta J(\theta) \approx \sum_i \nabla_\theta \log \pi_\theta(\mathbf{a}_i|\mathbf{s}_i) \hat{A}^\pi(\mathbf{s}_i, \mathbf{a}_i)$
 5. $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$

online actor-critic algorithm:

- 
1. take action $\mathbf{a} \sim \pi_\theta(\mathbf{a}|\mathbf{s})$, get $(\mathbf{s}, \mathbf{a}, \mathbf{s}', r)$
 2. update \hat{V}_ϕ^π using target $r + \gamma \hat{V}_\phi^\pi(\mathbf{s}')$
 3. evaluate $\hat{A}^\pi(\mathbf{s}, \mathbf{a}) = r(\mathbf{s}, \mathbf{a}) + \gamma \hat{V}_\phi^\pi(\mathbf{s}') - \hat{V}_\phi^\pi(\mathbf{s})$
 4. $\nabla_\theta J(\theta) \approx \nabla_\theta \log \pi_\theta(\mathbf{a}|\mathbf{s}) \hat{A}^\pi(\mathbf{s}, \mathbf{a})$
 5. $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$

Proximal Policy Optimization

- We don't want the new policy to change a lot in an iteration.
Why?

$$D_{KL}(\pi_{\theta'}(.|s) || \pi_{\theta}(.|s)) \leq \epsilon$$

- What is the effect of the constraint?
- Recall KL-Divergence:

$$D_{KL}(\pi_{\theta'}(.|s) || \pi_{\theta}(.|s)) = \sum_a \pi_{\theta'}(a|s) \log \frac{\pi_{\theta'}(a|s)}{\pi_{\theta}(a|s)}$$

We are effectively constraining the ratio $\frac{\pi_{\theta'}(a|s)}{\pi_{\theta}(a|s)}$